

Super Thin FFU

1 The super thin outlook design

It is 100mm thinner than the ordinary FFU. The material of cabinet is stainless steel, galvanized steel with aluminum painting, cold rolled steel with epoxy powder and so on. It is very light, corrosion-resistance, rust-resistance and beautiful.

2 Overheating protection

Inside equipped with overheating protection, the surface is smooth and bright, lower air resistance and good sound insulation. Special air entrance design and low down the noise effectively.

3 The average air speed increased by 25%


Long lifespan, low noise, small vibration and adjustable speed. The average air speed increase by 25%.

4 Prolonging lifespan

It works as an average air speed of 0.45m/s. The outlet speed is stable, and it can shorten the time of replacing filters. In the meantime, it can extend the service life of fans.


5 Oversized filter design, intergrated type

Light weight, concise, beautiful structure design, greatly reduced the use of space, more effective. It not only enhance the scope and space, but also save a lot of resources.






Product Parameter

Model	FUST-1	FUST-2	FUST-2	
Module size (WxLxHmm)	599x599x260	599x904x260	599x1208x260	
Air chamber material	Stainless steel 430			
Air flow (m ³ /h) @ 0.45m/s	550	800	1100	
Air velocity (m/s)	0.35 ~ 0.55			
Total pressure (Pa)	230	230	230	
Power (W)	100	100	200	
Weight (kg)	14	21	28	
Noise dB (1 m below the HEPA filter)	55-63			
Vibration (mm/s)	0.2-0.7			
Power supply	220V/ 60Hz 1PH			
Control mode	Rotary switch speed control panel			
Options	differential pressure testing port / differential pressure gauge / differential pressure alarm / group control			
HEPA filter	Size (WxHxDmm)	594x594x70	899x594x70	594x1203x70
	Efficiency	99.99%@0.3um		
	Frame	High quality anodized aluminum		
	Initial pressure drop	110Pa@0.45m/s±15%		
	Trait	PU foam endless gasket		



Parameter:

1. Handle (plastic)
2. AC EBM fan motor (220V/60Hz/1PH 115W)
3. Rotary switch speed control panel
4. HEPA filter, normal gasket filter, 1203x1203x70
5. Screw hook for HEPA filter





Items:

1. Handle (plastic)
2. AC EBM fan motor (220V/60Hz/1PH 100W) - 1
3. HEPA filter, normal gasket filter, 899x594x70
4. Screw hook for HEPA filter
5. Power cord connector
6. Rotary switch speed control panel

Standard Quality C

KLC®
KINGLANDCLEAN





Items:

1. Handle (plastic)
2. AC EBM fan motor (220V/60Hz/1PH 100W) - 1set
3. HEPA filter, normal gasket filter, 594x594x70
4. Screw hook for HEPA filter
5. Power cord connector
6. Rotary switch speed control panel

Standard Quality Control

KLC[®]

KINGLANDS CLEAN



- ns:
- Handle (plastic)
 - 2 EBM fan motor (220V/60Hz/1PH 100W) - 2sets
 - HEPA filter, normal gasket filter, 594x1203x70
 - crew hook for HEPA filter
 - power cord connector

